



广州市好印新材料科技有限公司

Guangzhou Haoyin New Material Technology Co., Ltd.

## PA0610 Digital Printable Heat Transfer Vinyl

### APPROVAL PAGE

Document Date: January 3, 2026

### TABLE OF CONTENTS

#### I. Product Features & Applications

#### II. Technical Parameters

#### III. Specifications & Packaging

#### IV. Storage & Shelf Life

#### V. Precautions

1、 Publishing Platform: DingTalk

2、 Authorized Access: All staff; Download permission: Department supervisors and above

3、 Implementation & Training: Business Department

4、 Revision Conditions:

A. Process changes; B. Material changes; C. Personnel changes in three-level approval positions

5、 Original Document Archive: General Office Archives

Prepared by: Li Jiexiang      Development Department III      Date: 2026-01-03

Prepared by: Li Jiexiang      Marketing Department      Date: 2026-01-03

Approved by: Xu Qinghai      CEO or Authorized Person      Date: 2026-01-03



# 广州市好印新材料科技有限公司

Guangzhou Haoyin New Material Technology Co., Ltd.

## PA0610 Digital Printable Heat Transfer Vinyl

TDS--Product Application Information

### I. Product Features & Applications

- 1、 Benefits: Combined with UV printing technology, perfectly solves traditional 3D labels' problems of "high cost for small batches, weak customization, and long production cycles." Suitable for wider application scenarios. Full-color fine patterns + 3D tactile feel, with visual effects superior to traditional 3D labels.
- 2、 Characteristics: Material mainly PU and TPU, soft and elastic.
- 3、 Advantages: Ultra-thin design, ultra-thin thickness maximizes restoration of fabric's original texture. Compatible with UV printing, supports CMYK + White Ink + Varnish full-color output. Can accurately reproduce various pattern details with high color saturation.
- 4、 Applications: Suitable for textile fabrics and leather. Compatible with both blade cutting and laser cutting.
- 5、 Limitations: For applications requiring high coverage, please select products with greater thickness. Pay attention to selecting compatible UV inks. Best results achieved with QINGYI UV inks.

### II. Technical Parameters

Test Item	Method/Equipment	Unit	Standard Value
Thickness	Digital Thickness Gauge	μm	60μm±10
Color Difference (Same Batch)	Handheld Spectrodensitometer	/	ΔE<1.5
Peel Force	internal	N/inch	0.1~2.5
Clarity	Visual Inspection	/	Clear and complete heat transfer, no burrs, hollows, delamination, or overflow
Abrasion Resistance	Print Ink Rub Tester	%	≥80
Wash Resistance	Home Washing Machine, Cold Water, 30 min	次	5+

#### Heat Press Conditions:

Temperature 150°C, Time 15s, Pressure 3.0 kgf/cm<sup>2</sup>. Cover pattern with fabric or release paper/film during transfer.

Note: Peel force refers to the separation force between color layer and adhesive film before heat pressing.

### III. Specifications & Packaging

Standard size: 60 cm × 25 m. Other custom specifications available upon request.

### IV. Storage & Shelf Life

- 1、 Store in a cool, dry place away from direct sunlight. Avoid high temperatures (above 40° C) and high humidity

Address: Room.309, No.9 Shenzhou Road, Huangpu District, Guangzhou, Guangdong Province, China.  
Hotline: 020-31701916  
gzhaoyin.com

Email: info@gzhaoyin.com  
Postal Code: 510663



广州市好印新材料科技有限公司

Guangzhou Haoyin New Material Technology Co., Ltd.

(above 70% RH).

- 2、 Prevent contact with sharp objects. Reseal unused portions after opening.
- 3、 Shelf life: 12 months under proper packaging and storage conditions. Verify product performance after expiration date before use.

## V. Precautions

- 1、 Product data provided for reference only. Users should conduct thorough validation and evaluation of product suitability for specific applications (purpose and conditions) prior to use.
- 2、 Wrinkles, dirt, dust, and moisture on the substrate surface may affect transfer results. Clean and iron the surface before use.
- 3、 This product disclaimer excludes liability for any incidental or consequential damages.

Address: Room.309, No.9 Shenzhou Road, Huangpu District, Guangzhou, Guangdong Province, China.  
Hotline: 020-31701916  
gzhaoyin.com

Email: info@gzhaoyin.com  
Postal Code: 510663